

Rinstrum Remotes Comparison

Model	Ingress Protection	Panel Mount	AC 110-240V Internal	DC 12-24V Internal	Internal NiMH Battery	Enclosed Housing	RS232 Ports	RS485 Ports	M/E Connectivity	Display Resolution	Display size	Physical size mm LxHxD	Package weight	Display update rate	Baud rate	Bracket	Software	Unit Switching	Zigbee Master/Slave	Ethernet	Remote Traffic Light Control by software	Remote Traffic Light Control by USB wired/Serial	Remote Traffic Light Control by USB wireless	Scrolling Display Control by 5-12V	Auto Brightness Control	Approvals	Protocols		
 D320 (ABS)	IP65					A		A		A		160 x 75 x 30mm (6.3 x 2.3 x 1.2in)	0.34kg (0.8lb)				A											Ranger A (GSE, HBM, PT, Rinstrum, Systec), Ranger B/D(Rinstrum), Ranger C(GSE, HBM, PT and Rinstrum), PCMODE(Custom software), R series register write(GSE, Rinstrum ), Avery string #7(Avery L105), Gedge C2/C3(Gedge), AD standard string(A & D ), AD4531 (A & D), Toledo continuous(Toledo), GSE with/without COZ (GSE), Schenck with/without DP(Schenck), Auto control string 1/2(Auto control), Sartorius (Sartorius ), Soehnle with/without DP(Soehnle), Flintab(Flintab), Philips(Philips), Condec(UMC, GSE, Rice Lake, Cardinal, Fairbanks, Eaton, Transcell), Rice Lake SCT(Rice Lake)	
 D323 (Stainless Steel)	IP65							A	S	*A	Single line 6 digits	20mm (0.8in) LCD with backlight	200 x 115 x 30mm (7.9 x 4.6 x 1.2in)	0.49kg (1.1lb)	10Hz	9600,19200 auto detecting				kg,g,lb,t	-	A	-	-	-	-	-		C-Tick, CE & FCC
 XD30 (Plastic Alloy)	IP69K IP68			*	**	12V 2.5Ah		S				250 x 131 x 115mm (9.9 x 5.2 x 4.6in)	2.0kg (4.5lb)				Included												
 6700A (Aluminium)	IP51/ Panel IP65	A	A	A			A	S	A	S	A	Single line 6 digit 7 seg	14.5mm (0.6in) Green LED	150 x 72 x 100mm (6 x 2.9 x 4in)	1.1kg/0.625kg (2.5lb/1.4lb)	10Hz	300 to 19200			kg,g,lb,t	-	A	A	A	A	-	-		Rinstrum,Avery,Gedge,A&D,Toledo,Barlo,Lodec, Philips 1577, 1627
 D732 (Aluminium)	IP65			S			S	S	S	A	7 seg LED	75mm (3in)	488 x 150 x 80mm (19.2 x 6 x 3.2in)	3.3kg (7.3lb)	-	9600		Included	K700									C-Tick, CE & FCC	Rinstrum and Condec
 D841 (Aluminium)				*	**			S				100mm (4in)	770 x 150 x 80mm (30.3 x 6 x 3.2in)	4.6kg (10.2lb)														Ranger A(Rinstrum, GSE, HBM & PT), Ranger B/D(Rinstrum), Ranger C(Rinstrum GSE, HBM & PT), PCMODE(Custom software), RINCM/MD(Rinstrum & GSE), Avery string #7(Avery L105), Gedge C2/C3(Gedge), A&D standard string(A&D), AD4531(A&D), Toledo continuous(Toledo), GSE with/without COZ(GSE), Schenck with/without DP(Schenck), Auto control string 1/2(Auto control PC Software), Sartorius (Sartorius), Soehnle with/without DP(Soehnle), Flintab(Flintab), Philips(Philips), Condec(UMC, GSE, Rice Lake, Cardinal, Fairbanks, Eaton, Transcell), Bilancial D5410(Bilancial), Systec(System), Configuration(Changing settings), Scrolling(K802 firmware only)	
 D850	IP65			*	**			S	S		Full Matrix		811 x 200 x 90mm (32 x 7.9 x 3.2in)	7.4 kg (16.3lb)							kg,g,lb,t	A	A	-	A				S

\* Convert RS232 port to RS485 with a 0080  
 \* Factory AC option  
 \*\* Factory DC option